







SPECIFICATIONS

Description	Loc8tor System – Portable dual function locating system
Key Applications	Finding personal belongings & preventing them from getting lost in the first place Potential uses include keys, wallets, mobile phones, pets & children (Alert mode)
Range	Up to 600 feet / 183m to within 1" (2.5cm) – Range based on clear line of sight Actual range will vary depending on use and location
Tag Personalisation	Plus - Name each tag using up to 10 characters
Operational Temperature	0C to + 55C. Store between -10C and +60C
Awards	http://www.loc8tor.co.uk/Store/Awards.aspx
Certification	CE, FCC & IC approved. RoHS & WEEE compliant

	 Loc8tor Lite	 Loc8tor Plus Pack	 Homing Tag	 Panic Tag
Pack contains	Loc8tor Lite Handheld, 2 x mini Homing Tags, magnetic wall bracket, adhesive strips, key ring loops, user guide. Batteries included	Loc8tor plus Handheld, 3 x mini Homing Tags, 1 x Panic Tag, adhesive strips, key ring loops, user guide. Batteries included	2 x mini Homing Tags, Key ring loops & adhesive strips	2 x mini Homing Tags, key ring loops & adhesive strips
Maximum tags	4	24	N/A	N/A
Modes	Locate	Locate / Alert	Homing Tag – Can Locate & Alert depending on Handset	Homing Tag with Panic button – Can Locate & Alert. Designed for use with Loc8tor Plus
Dimensions	86mm x 54mm x 6mm 3.4" x 2.13" x 0.23 inches	110 x 53 x 16mm 4.3 x 2.1 x 0.6 inches	30.5 x 19.5 x 8.5mm 1.2 x 0.8 x 0.3 inches	30.5 x 19.5 x 8.5mm 1.2 x 0.8 x 0.3 inches
Sound	Variable pitch & frequency to locate object	Up to 90 dB Alarm. Variable pitch & frequency to locate object	Audio beeps	Audio beeps
Light	Red, Orange & Yellow LED to guide users to lost object	Illuminated LCD screen	LED flashes to indicate activated	LED flashes to indicate activated
Vibration	No	Vibrator motor used in Alert sequence	N/A	N/A
Batteries	Handset requires 1xCR2032 Lithium cell battery	Handset requires 2 x AAA 1.5 volt alkaline cells	2 x SR54 (silver oxide) 1.5 volt button cells or equivalent	2 x SR54 (silver oxide) 1.5 volt button cells or equivalent
Packaging	Box 20x10x200 cm 7.75x3.9x0.9 inches	Box 43 x 180 x 160mm 1.7 x 7.1 x 6.3 inches	Box 16 x 83.5 x 145.5mm 0.69 x 3.28 x 5.7 inches	Box 16 x 83.5 x 145.5mm 0.69 x 3.28 x 5.7 inches
Shipping Cases	Boxed in 10's. 60 packs / outer case, measurements 44.4 x 35.5 x 28.5cm (17.76 x 14.2 x 11.4 inches). 30 Outers / pallet Outer Case Weight : 8.1KG	Boxed in 6's. 24 packs / outer case, measurements 276 x 376 x 349mm (10.8 x 14.8 x 13.7 inches). 30 Outers / pallet Outer Case Weight: 7.8 KG	Boxed in 10's. 100 packs / outer case, measurements 438 x 307 x 182mm (17.2 x 12.1 x 7.2 inches). Outer Case Weight: 7.3 KG	Boxed in 10's. 100 packs / outer case, measurements 438 x 307 x 182mm (17.2 x 12.1 x 7.2 inches). Outer Case Weight : 7.3 KG

The above specifications, while correct at April 2009, are subject to change. No information set out to in this document including, without prejudice, the specifications, shall form the basis of any contract. © Locator 2009 www.loc8tor.co.uk :: +44 (0) 208 207 0880