





LOC8TOR SPECIFICATIONS

Description	Loc8tor System – Portable dual function homing device
Key Applications	Finding personal belongings & preventing them from getting lost in the first place Potential uses include keys, wallets, mobile phones, pets & children (Alert mode)
Range	Up to 600 feet / 183m to within 1" (2.5cm) – Range based on clear line of sight Actual range will vary depending on use and location
Tag Personalisation	Name each tag using up to 10 characters
Operational Temperature	0C to + 55C. Store between -10C and +60C
Awards	Innovations 2006 International CES Design & Engineering Honours
Certification	CE, FCC & IC approved.

	Loc8tor Pack 	Loc8tor Plus Pack 	Homing Tag 	Panic Tag 
Pack contains	Loc8tor Handheld, 2 x mini Homing Tags, adhesive strips, Key ring loops, user guide. Batteries included	Loc8tor plus Handheld, 3 x mini Homing Tags, 1 x Panic Tag, adhesive strips, key ring loops, user guide. Batteries included	2 x mini Homing Tags, Key ring loops & adhesive strips	2 x mini Homing Tags, key ring loops & adhesive strips
Maximum tags	24	24	N/A	N/A
Modes	Locate	Locate / Alert	Homing	Homing / Panic button
Upgrades	Alert mode. Also Asset protection from September production	Asset protection mode (up to 6000 numbered tags) from September production	N/A	N/A
Dimensions	110 x 53 x 16mm 4.3 x 2.1 x 0.6 inches	110 x 53 x 16mm 4.3 x 2.1 x 0.6 inches	30.5 x 19.5 x 8.5mm 1.2 x 0.8 x 0.3 inches	30.5 x 19.5 x 8.5mm 1.2 x 0.8 x 0.3 inches
Sound	Up to 90 dB. Variable pitch & frequency to locate object	Up to 90 dB. Variable pitch & frequency to locate object	Audio beeps	Audio beeps
Light	Illuminated LCD screen	Illuminated LCD screen	LED flashes to indicate activated	LED flashes to indicate activated
Vibration	Vibrator motor used when upgraded to Loc8tor plus	Vibrator motor used in Alert sequence	N/A	N/A
Batteries	Handset requires 2 x AAA 1.5 volt alkaline cells	Handset requires 2 x AAA 1.5 volt alkaline cells	2 x SR54 (silver oxide) 1.5 volt button cells or equivalent	2 x SR54 (silver oxide) 1.5 volt button cells or equivalent
Packaging	Box 43 x 180 x 160mm 1.7 x 7.1 x 6.3 inches	Box 43 x 180 x 160mm 1.7 x 7.1 x 6.3 inches	Box 16 x 83.5 x 145.5mm 0.69 x 3.28 x 5.7 inches	Box 16 x 83.5 x 145.5mm 0.69 x 3.28 x 5.7 inches
Shipping Cases	Boxed in 6's. 24 packs / outer case, measurements 276 x 376 x 349mm (10.8 x 14.8 x 13.7 inches). 30 Outers / pallet	Boxed in 6's. 24 packs / outer case, measurements 276 x 376 x 349mm (10.8 x 14.8 x 13.7 inches). 30 Outers / pallet	Boxed in 10's. 100 packs / outer case, measurements 438 x 307 x 182mm (17.2 x 12.1 x 7.2 inches).	Boxed in 10's. 100 packs / outer case, measurements 438 x 307 x 182mm (17.2 x 12.1 x 7.2 inches).

The above specifications, while correct at March 2006, are subject to change. No information set out to in this document including, without prejudice, the specifications, shall form the basis of any contract. © Locator 2006